PTO/SB/21 (08-00) Approved for use through 10/31/2002, OMB 0651-0031

U.S. Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number. **Application Number TRANSMITTAL Filing Date** FEB 5 2003 **FORM First Named Inventor** (to be used for all correspondence after initial filing) Group Art Unit **Examiner Name** Attorney Docket Number Total Number of Pages in This Submission (check all that apply) **ENCLOSURES** After Allowance Communication **Assignment Papers** Fee Transmittal Form (for an Application) to Group Appeal Communication to Board Fee Attached Drawing(s) of Appeals and Interferences Appeal Communication to Group Licensing-related Papers Amendment / Reply (Appeal Notice, Brief, Reply Brief) Petition After Final Proprietary Information Petition to Convert to a Affidavits/declaration(s) **Provisional Application** Status Letter Power of Attorney, Revocation Change of Correspondence Other Enclosure(s) (please Extension of Time Request Address identify below): Terminal Disclaimer **Express Abandonment Request** Request for Refund Information Disclosure Statement CD, Number of CD(s). Certified Copy of Priority Document(s) Remarks RECEN/ Response to Missing Parts/ Incomplete Application FEB 0 7 2003 Response to Missing Parts under 37 CFR 1.52 or 1.53 TECHNOLOGY CENTER R3700 SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT Firm Individual name Signature Date **CERTIFICATE OF MAILING** I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, Washington, DC 20231 on this date: Typed or printed name Signature Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.



First Inventor: Howard F. Gokey (518) 483-5525

Contents January 27, 2003

Abstract	Page 1
Title of Invention	Page 2
Specifications	Page 2
Cross Reference to Related Applications	Pages 3-4
Statement Regarding Federally Sponsored Research or Development	Page 5
Reference to sequence Listing, a Table, or Computer Program Listing Compact Disk Appendix	Page 6
Field of Invention	Page 7
Background of Invention	Page 7
Brief Summary of the Invention	Page 8
Brief Description of Drawings	Page 9
Drawings & Photographs Figure 1A Figure 2A	_
Detailed Description of the Invention	Page 12
Claims	Page 13

RECEIVED

FEB 0 7 2003



First Inventor: Howard F. Gokey (518) 483-5525

ABSTRACT January 27, 2003

The Bar Clamp Corner Squaring Fixture hereinafter called "Adaptor" is used in conjunction with a beam clamping assemblies to hold and lock in place a plurality of frame members.

The Adaptor provides a unique method of using existing beam clamping assemblies to clamp frame members and allow them to be glued and held in square while the glue dries.

The Adaptor is designed to be unattached from the bar clamp assembly that provides the clamping function. This facilitates the Adaptor to be used on a plurality of different beam clamping assemblies. The Adaptor can be easily adjusted by simply moving the bar clam jaws to hold both small and large size frames.

The Adaptor is used by itself and requires no additional fixtures to complete the function of maintaining a plurality of frame members in a square position in a bar clamping assembly.

RECEIVED

FEB 0 7 2003



First Inventor: Howard F. Gokey (518) 483-5525

Specification of Invention January 27, 2003

Title of Invention: Bar Clamp Corner Squaring Device

First Inventor: Howard F. Gokey

U.S. Citizen 25 Edward Street Malone NY, 12953

Specification:

The invention consist of four (4) pieces of metal fabricated to 90 degree corners and is used in conjunction with beam clamp assemblies. Drawings (Figures 1A and 2A) describing the bar Clamp Corner Squaring Devices in detail are attached

The metal fixtures are made from 1/8" band iron and are welded in the corners and at the base.

The fixtures are 1 1/4" high and each side is 3 1/2" long.

The four (4) corner pieces were designed to be used to hold picture frames in place and in square to allow them to be glued. Cardboard or paper can be placed over the fixtures to prevent excess glue from getting on the fixtures.

People familiar with this art will be able to use the devices easily.

RECEIVED

FEB 0 7 2003



First Inventor: Howard F. Gokey (518) 483-5525

Cross Reference to Related Applications January 27, 2003

Related U.S. Application Data

Division of applications No. 08/787,971. Jan 23, 1997

Int. Cl	B25B 1/24
	269/168; 269/282; 269/283; 260/147
Field of Search	254/41, 147-149, 254/166-171.5,
	203-206 282 283 279 280 88 45

Reference Cited – U.S. PATENT DOCUMENTS

RE:	34,953	5/1995	Delaney et al.,
	641,694	1/1900	Hamelehle,
	665,398	1/1901	Broadbooks,
	800,685	10/1905	Scoggins,
	890,063	6/1908	Jones,
	1,015,171	1/1912	Goble,
	1,498,638	6/1924	Periolat,
	1,669,493	5/1928	Billstrom,
	2,258.686	10/1941	Olney,
	2,340,316	2/1944	Fest,
	3,154,304	10/1964	Crawford,
	3,403,901	10/1968	Servadio,
	3,499,206	3/1970	Quernheim,
	3,767,183	10/1973	Van Gelder,
	4,052,046	10/1977	Mortoly,
	4,068,834	1/1978	Mortloy,
	4,134,578	1/1979	Stanley,
	4,363,475	12/1982	McCarty
	4,437,654	3/1984	Chiappetti,
	4,583,724	4/1980	Huang,
	4,662,618	5/1987	Willis,
	4,779,857	10/1988	Manual,
	4,898,371	2/1990	Mills et al.,
	4,921,234	5/1990	Peterson
	4.923,186	5/1990	Drfee, Jr.,



Reference Cited - U.S. PATENT DOCUMENTS (Continued)



	0/1000	371 1 1
4,953,840	9/1990	Nishimura,
5,002,264	3/1991	Nimtz,
5.064,178	11/1991q	Nimtz,
5,129,350	7/1992	Marelin,
5,153,665	11/1992	Klearman,
5,246,216	9/1993	Oberst,
5,443,245	8/1995	Peterson,
6.039.313	3/2000	Baculy.

FOREIGN PATENT DOCUMENTS

0300473	7/1988	European Pat. Off.,
110453	1/1899	Germany,
1269967	3/1967	Germany,
8700775	1/1987	Germany,
3631048	4/1987	Germany,
9112721	3/1989	Germany,
322734	8/1957	Switzerland.

RECEIVED
FEB 0.7 2003
TECHNOLOGY CENTER 93700



First Inventor: Howard F. Gokey (518) 483-5525

Statement Regarding Federally Sponsored Research or Development January 27, 2003

Not Applicable

RECEIVED

FEB 0 7 2003



First Inventor: Howard F. Gokey (518) 483-5525

Reference to Sequence Listing a Table, or a Computer Program Listing Compact Disk Appendix January 27, 2003

Not Applicable

RECEIVED

FEB 0 7 2003



First Inventor: Howard F. Gokey (518) 483-5525

Clamp Fixtures January 27, 2003 RECEIVED

FEB 0 7 2003

This is a continuance to application Number 10/084,786, filed of the Penter R3700

Field of the Invention

This invention relates to clamp fixtures of the type used in association with pipe clamps and bar clamps and more particularly to clamping systems which are easily changed to facilitate use of any of a number of different clamping devices which are specifically adapted for clamping certain types of work pieces or other articles.

Background of Invention

Pipe clamp assemblies and bar clamp assemblies hereinafter referred to as beam clamp assemblies. Beam Clamp assemblies are commonly used to hold work pieces or other articles in a fixed position to allow for other operations such as cutting, drilling, nailing, screwing, gluing etc. Beam clamp assemblies usually consist of a linear beam (e.g. pipe, rod, or bar) and a pair of opposing jaws, one of which is fixed to the beam at one location and the other while being attached can be moved by sliding it along the beam. The ability to slide one of the jaws allows for the jaw to apply and relive pressure. Normally the jaws are made in a manner that provides for them to have parallel opposing gripping surfaces. This allows the bar clamping assemblies to clamp work pieces and other items having flat parallel opposing surfaces. However, these clamping devices cannot hold the work pieces or other articles in a square position that is often required. For example, to grip the corner of picture frames specialty configured miter jigs having mitered gripping surfaces have been designed. These specialty jigs have been provided with fasteners that allow the jigs to be attached to the jaws of the beam clamp assembly. These fasteners cause a disadvantage as they require to be attached to a particular type beam assembly and cannot be used interchangeably with the standard beam clam assembly. Other clamping devices also require attachment of multiple jigs to clamp work pieces or other items. This lack of interchangeably and requirement of multiple jigs can be a great disadvantage to workers who must match jigs for a particular job to a particular type of beam clamp assembly which may or may not be available and cause loss of time.

It is desirable that jigs or other fixtures used for clamping be versatile to allow for clamping with out need to attach special jigs to a bar clamping assembly or need to attach multiple jigs to a bar clamp assembly and still be able to hold the work pieces in square. This is extremely important in the assembly of picture frames.



First Inventor: Howard F. Gokey (518) 483-5525

Summary of the Invention January 27, 2003

This invention is unique as it provides adaptors that do not require attachment to the beam clamp assembly but utilize them to clamp work pieces or other items in a square manner. To utilize the functionality of this invention it is required that 4 adaptors be used and 4 beam clamps. The smooth surface minimizes scarring and the strength of the 90 degree welded corned assures that the clamped work piece will be maintained in a square fashion.

The usage of these adaptors provides great flexibility in clamping a myriad of sized work pieces. Changing the length or width to accommodate a large or small size work piece can be done without changing out any specialized clamping fixture. It only requires that the position of the adjustable jaw on the beam clamping assembly be moved.

If gluing is required, the adaptors can be protected with a piece of paper or cardboard which can be discarded once the work piece has sufficiently cured.

The adaptors are small in size and do not require much storage space as they can be nested.

RECEIVED

FEB 0 7 2003



First Inventor: Howard F. Gokey (518) 483-5525

Drawings January 27, 2003


There are two drawings attached:


Drawings:


Figure 1A: Shows the adaptor separately and on one beam clamp assembly. Provided dimensional information for the adaptors.


Figure 2A: Shows all four adaptors in place and how they would be clamped with four beam clamp assemblies.


RECEIVED
FEB 0 7 2003
TECHNOLOGY CENTER HS/00











-10-

BAR CLAMP CORNER SQUARING FIXTURE FIGURE 2A Fifth Threath: Howard F. Golfey (518) 483-5525 FEB 0 5 2003 (1) (3) (Z) CLAMP 量(7) NOTE : DRIVINGS



First Inventor: Howard F. Gokey

(518) 483-5525

Detailed Description of the Invention January 27, 2003

This invention is to be used to hold frames in square while they are being glued. They are very easy to use and do not require any attachment to the jaws of beam clamping devices.

One who is has just ordinary skill in the art of frame making will be familiar enough with the art and will only have to do the following to utilize the functionality of the Bar Clamp Corner Squaring devices. (Refer to Drawing Figure 2A for part number references.)

- 1) Place two beam clamping devices on a flat surface. (Parts 1 & 2)
- 2) Set Bar Clamp Corner Squaring devices into the jaws of two beam clamping devices. (Parts 3, 4, 5, 6)
- 3) Insert the frame members that they wish to assemble. (Parts not shown)
- 4) Apply glue to the ends of the frame members
- 5) Adjust the beam clamping jaws to apply pressure on the assembled frame members.
- 6) Place two additional beam clamping devices perpendicular to the initial ones and adjust by clamping to the beams of the first two devices. (Parts 7 & 8)
- 7) Tighten beam clamping devices to ensure that assembled frame is in square.
- 8) Wait a sufficient time period to allow the glue to dry
- 9) Remove beam clamping devices and the Bar Clamp Corner Squaring devices.

The invention ease of use and ability to be used with beam clamping devices without being fastened to them provide it with versatility. Other clamping devices require attachment to the beam clamping devices or attachment to attachments.

The strength of the 90 degree welded corned assures that the clamped work piece will be maintained in a square fashion. The two sides of the device are individually welded to the bottom pieces well as being welded to each other.

The Bar Clamp Corner Squaring devices are easily stored and can be nested together to save space.

`(,



First Inventor: Howard F. Gokey (518) 483-5525

Claim January 27, 2003

What is claimed is:

- 1) A clamping system comprising of:
 - a first beam clamp including a beam and a pair of opposing jaws;
 - a second beam clamp including a beam and pair of opposing jaws;
 - a set of four unattached adaptors designed to nest into the first and second beam opposing jaws;
 - a third beam clamp including a beam and a pair of opposing jaws;
 - a fourth beam clamp including a beam and a pair of opposing jaws.
- 2) The four adaptors of clamping system of Claim 1 provide a squaring fixture when used with the four beam clamping devices.
- 3) The four adaptors of clamping system of Claim 1 are not required to be attached to the opposing jaws to perform their squaring function.
- 4) The four adaptors are adjustable by moving the opposing jaws of the clamping system of Claim 1
- 5) The third and forth beam clamps in Claim 1 positioned perpendicular to the first and second beams in Claim 1 align the work piece into square.

Claims made by:

Howard F. Gokev

. — —

FEB 0 7 2003